


Rolls AGM 12V Deep Cycle Sealed Maintenance Free AGM Battery

CUT OFF VOLTAGE V/CELL	15M	30M	1HR	2HR	3HR	5HR	8HR	10HR	20HR
10.5V	154	102	60.6	32.5	28	16.4	10.6	9	5

RESERVE CAPACITY		CCA	
@25AMPS	@75 AMPS	CCA@0°C	CCA@-18°C
205 Mins.	50 Mins.	1050	850

SPECIFICATIONS		
Nominal Voltage		12 Volt
Rated Capacity (20 hour rate)		110 Ah
Dimensions	Total Height (including terminals)	240mm
	Height	220mm
	Length	328mm
	Width	172mm
Weight		30.0 Kg



CHARACTERISTICS		
Capacity 77°F (25°C)	100 Hour Rate	120 Ah
	20 Hour Rate	110 Ah
	10 Hour Rate	90 Ah
Internal Resistance	Full charged Battery 77°F (25°C)	9mΩ
Capacity Affected by Temperature (20hr rate)	104°F (40°C)	102%
	77°F (25°C)	100%
	32°F (0°C)	85%
	5°F (-15°C)	65%
Self Discharge 77°F (25°C)	Capacity after 3 month storage	91%
	Capacity after 6 month storage	82%
	Capacity after 12 month storage	64%
Max Discharge 77°F (25°C)	1600A (5s)	
Terminal	Standard	M8-TP08
Charging (Constant Voltage)	Cycle	14.6 to 14.8V DC/unit Average at 25°C
	Float	13.6 to 13.8V DC/unit Average at 25°C

