



FLOODED DEEP CYCLE BATTERIES

2 YS 3IP

2 VOLTS



|                    |                                                       |
|--------------------|-------------------------------------------------------|
| CONTAINER: (INNER) | Polypropylene                                         |
| COVER: (INNER)     | Polypropylene - heat sealed to inner container        |
| CONTAINER: (OUTER) | High Density Polyethylene                             |
| COVER: (OUTER)     | High Density Polyethylene snap fit to outer container |
| TERMINALS:         | Flag with stainless steel nuts & bolts                |
| HANDLES:           | Molded                                                |

|             |        |               |
|-------------|--------|---------------|
| WEIGHT DRY: | 91 kg  | 200 Lbs.      |
| WEIGHT WET: | 129 kg | 285 Lbs.      |
| LENGTH:     | 394 mm | 15 1/2 Inches |
| WIDTH:      | 229 mm | 9 Inches      |
| HEIGHT:     | 803 mm | 31 5/8 Inches |

|                                                                                  |         |               |
|----------------------------------------------------------------------------------|---------|---------------|
| PLATE HEIGHT:                                                                    | 600 mm  | 23.625 Inches |
| PLATE WIDTH:                                                                     | 143 mm  | 5.625 Inches  |
| THICKNESS (POSITIVE):                                                            | 6.99 mm | 0.275 Inches  |
| THICKNESS (NEGATIVE):                                                            | 4.57 mm | 0.180 Inches  |
| POSITIVE PLATE DOUBLE WRAPPED WITH SLYVER<br>ENVELOPED WITH HEAVY DUTY SEPARATOR |         |               |




|                                      |                |              |
|--------------------------------------|----------------|--------------|
| CELLS:                               | 31 Plates/Cell | 1 Cell       |
| SEPARATOR THICKNESS:                 | 3 mm           | 0.105 Inches |
| GLASS MAT INSULATION:                | 1 mm           | 0.022 Inches |
| ELECTROLYTE RESERVE:<br>ABOVE PLATES | 95 mm          | 3.75 Inches  |

|                              |               |              |
|------------------------------|---------------|--------------|
| COLD CRANK AMPS (CCA):       | 0°F / -17.8°C | 5740         |
| MARINE CRANK AMPS (MCA):     | 32°F / 0°C    | 7175         |
| RESERVE CAPACITY (RC @ 25A): |               | 8193 Minutes |


## CAPACITY 2430 AH

| HOURLY RATE:    | SPECIFIC GRAVITY | CAPACITY / AMP HOUR | CURRENT / AMPS |
|-----------------|------------------|---------------------|----------------|
| @ 100 HOUR RATE | 1.280            | 3426                | 34.26          |
| @ 72 HOUR RATE  | 1.280            | 3232                | 44.89          |
| @ 50 HOUR RATE  | 1.280            | 2989                | 59.78          |
| @ 24 HOUR RATE  | 1.280            | 2527                | 105.30         |
| @ 20 HOUR RATE  | 1.280            | 2430                | 121.50         |
| @ 15 HOUR RATE  | 1.280            | 2260                | 150.66         |
| @ 12 HOUR RATE  | 1.280            | 2114                | 176.18         |
| @ 10 HOUR RATE  | 1.280            | 2017                | 201.69         |
| @ 8 HOUR RATE   | 1.280            | 1895                | 236.93         |
| @ 6 HOUR RATE   | 1.280            | 1725                | 287.55         |
| @ 5 HOUR RATE   | 1.280            | 1628                | 325.62         |
| @ 4 HOUR RATE   | 1.280            | 1507                | 376.65         |
| @ 3 HOUR RATE   | 1.280            | 1361                | 453.60         |
| @ 2 HOUR RATE   | 1.280            | 1166                | 583.20         |
| @ 1 HOUR RATE   | 1.280            | 826                 | 826.20         |

## CYCLE LIFE VS. DEPTH OF DISCHARGE



## VOLTAGE VS. DEPTH OF DISCHARGE



Amphère Hour capacity ratings based on specific gravities of 1.280. Reduce capacities 5% for 1.265 specific gravity and 10% for specific gravities of 1.250

WWW.ROLLSBATTERY.COM

SURRETTE BATTERY COMPANY 1 STATION RD SPRINGHILL, NS CANADA B0M 1X0

SPEC 01

1/1/2014 REV. 1